

**Product** 49130**Number:****Order** QTP 2X54T5HO/UNV PSN**Abbreviation:****General** 2- Lamp universal voltage electronic ballast for 54W T5 HO lamp.**Description:** Packaged 10 pieces per case with wires**Product Information**

Abbrev. With Packaging Info.	QTP2X54T5HO UNVPSN 10/CS 1/SKU
Ballast Factor	1.00
Ballast Height H (in)	0.8660
Ballast Length L (in)	16.6540
Ballast Width W (in)	1.1810
Circuit Type	SERIES
Family Brand Name	QUICKTRONIC Professional
Input Current (Amps)	0.50
Nominal Voltage (V)	120.00
Nominal Voltage (V)	120-277V
Number of Lamps	2
Open Circuit Voltage (V)	<600
Power Factor	>0.98
Primary Lamp Type	FP54T5HO
Sound Rating	A
Starting Method	PROSTART
Starting Temperature - Fahrenheit	-20
Starting Temperature - Celsius	-29
Total Harmonic Distortion (THD)	<10%
Wiring Method	WIRETRAP CONNECTORS
Total Maximum Wattage	121

**Footnotes**

- Data based on primary lamp types. See OSRAM SYLVANIA System Performance Guide for data on other lamp combinations.
- Product is a kit containing the core & coil, capacitor, ingitor (where required), brackets and mounting hardware
- Remote Mounting up to 18 feet
- Remote Mounting up to 12 feet
- Remote Mounting up to 10 feet
- Remote mounting defined by harness length

- Complies with FCC 47 CFR Part 18, Non-Consumer
- Remote Mounting up to 19 feet (keep red wires short for 1&2 lamp).
- Wiring diagram applies to instant start standard, low power (LP), PLUS, and HD10 ballast types.
- Oil Filled Capacitor
- Product contains installation instructions