



GE
Lighting

48864 - F57QBX/841/A/ECO

GE Ecolux® Biax® T4 - Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse

- Super long life



High Color Rendering
Energy Savings

Photo
Not Available



CAUTIONS & WARNINGS

Caution

- Lamp may shatter and cause injury if broken
 - Remove and install by grasping only plastic portion of the lamp.

NOTES

- 4-Pin lamp minimum starting temperature is a function of the ballast. Most ballasts are rated with a minimum starting temperature of 50 degrees F (10 C). Ballasts are also available that provide reliable starting to 0 degrees F (-18C) and -20 F (-29C).
- Amalgam product experience stable brightness over a wider temperature range and in various operating positions.
- Based on 60Hz reference circuit.
- Fluorescent lamp lumens decline during life

GENERAL CHARACTERISTICS

Lamp Type	Compact Fluorescent - Plug-In
Bulb	T4
Base	GX24-q5
Equivalent Wattage (NOM)	200.0 W
Rated Life (NOM)	17000.0 h
Starting Temperature (MIN)	-20.0 °C
Mercury Content (NOM)	3.0 mg
Picograms of Mercury (NOM)	47.69475 pg
Additional Info	Dimmable with appropriate dimming ballast./End of Life Protection (EOL)/TCLP compliant
Primary Application	Facilities;Retail Display;Hospitality;Office;Restaurant;W

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	4300.0
Mean Lumens (NOM)	3700.0
Nominal Initial Lumens per Watt (NOM)	75.4386
Color Temperature (NOM)	4100.0 K
Color Rendering Index (CRI) (NOM)	82.0

ELECTRICAL CHARACTERISTICS

Wattage (NOM)	57.0
Voltage (NOM)	120.0
Lamp Current (NOM)	0.32 A
Current Crest Factor (MAX)	1.7
Supply Current Frequency (NOM)	20.0 Hz

DIMENSIONS

Maximum Overall Length (MOL) (NOM)	7.100 in(180.3 mm)
Nominal Length (NOM)	7.100 in(180.3 mm)

PRODUCT INFORMATION

Product Code	48864
Description	F57QBX/841/A/ECO
ANSI Code	60901-IEC-7457-1
Standard Package	Case
Standard Package GTIN	10043168488645
Standard Package Quantity	10
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	10
UPC	043168488648