





GE  
Lighting

## 86271 - FLE15HT2/2/827

GE Spiral® T2



### GENERAL CHARACTERISTICS

Lamp Type	Compact Fluorescent - Self-Ballasted
Bulb	T2
Base	Medium Screw (E26)
Bulb Finish	Soft white
Equivalent Wattage (NOM)	60.0 W
Rated Life (NOM)	12000.0 h
Starting Temperature (MIN)	5.0 °C
Total Harmonic Distortion (THD) (NOM)	120.0 %
Mercury Content (NOM)	3.5 mg
Picograms of Mercury (NOM)	383.8 pg
Primary Application	Standard

### PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	950.0
Mean Lumens (NOM)	760.0
Nominal Initial Lumens per Watt (NOM)	63.33333
Color Temperature (NOM)	2700.0 K
Color Rendering Index (CRI) (NOM)	82.0

### ELECTRICAL CHARACTERISTICS

Wattage (NOM)	15.0
Input Voltage (NOM)	120.0 V
Input Current (NOM)	0.23 A
Power Factor (NOM)	0.5

### DIMENSIONS

Maximum Overall Length (MOL) (NOM)	4.100 in(104.1 mm)
Nominal Length (NOM)	4.100 in(104.1 mm)

### PRODUCT INFORMATION

Product Code	86271
Description	FLE15HT2/2/827
Standard Package	Case
Standard Package GTIN	10043168862711
Standard Package Quantity	10
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	10
UPC	043168862714

### NOTES

- Best performance if operated base up and at 77 degrees F (25C) ambient temperature.
- Fluorescent lamp lumens decline during life
- Lumens on one piece self ballasted lamp systems are measured base up.
- Most one piece self ballasted lamps for incandescent sockets and plug-in lamps with screw-in adapters do not work with clip-on shades
- Use only on 120V 60 Hz circuits. Do not use on dimming circuits, photocells or timers. Do not use in wet locations.