



GE
Lighting

93404 - F57QBX850A4P/EOL

GE Ecolux® Biax® T4 - Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse

- Super long life



High Color Rendering
Energy Savings

Photo
Not Available



CAUTIONS & WARNINGS

Caution

- Lamp may shatter and cause injury if broken
 - Remove and install by grasping only plastic portion of the lamp.

NOTES

- 4-Pin lamp minimum starting temperature is a function of the ballast. Most ballasts are rated with a minimum starting temperature of 50 degrees F (10 C). Ballasts are also available that provide reliable starting to 0 degrees F (-18C) and -20 F (-29C).
- Amalgam product experience stable brightness over a wider temperature range and in various operating positions.
- Based on 60Hz reference circuit.
- Fluorescent lamp lumens decline during life

GENERAL CHARACTERISTICS

Lamp Type	Compact Fluorescent - Plug-In
Bulb	T4
Base	GX24-q5
Equivalent Wattage (NOM)	200.0 W
Rated Life (NOM)	17000.0 h
Starting Temperature (MIN)	-20.0 °C
Mercury Content (NOM)	3.0 mg
Picograms of Mercury (NOM)	47.69475 pg
Additional Info	Dimmable with appropriate dimming ballast./End of Life Protection (EOL)/TCLP compliant
Primary Application	Facilities;Retail Display;Hospitality;Office;Restaurant;W

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	4300.0
Mean Lumens (NOM)	3700.0
Nominal Initial Lumens per Watt (NOM)	75.4386
Color Temperature (NOM)	5000.0 K
Color Rendering Index (CRI) (NOM)	82.0

ELECTRICAL CHARACTERISTICS

Wattage (NOM)	57.0
Voltage (NOM)	175.0
Lamp Current (NOM)	0.32 A
Supply Current Frequency (NOM)	20.0 Hz

DIMENSIONS

Maximum Overall Length (MOL) (NOM)	5.200 in(132.1 mm)
Nominal Length (NOM)	5.200 in(132.1 mm)

PRODUCT INFORMATION

Product Code	93404
Description	F57QBX850A4P/EOL
ANSI Code	60901-IEC-7457-1
Standard Package	Case
Standard Package GTIN	10043168934043
Standard Package Quantity	10
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard	10
Package	
UPC	043168934046