

# 97596 - F13DBX/835/ECO4P

GE Ecolux® Biax® T4 - Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse










## **CAUTIONS & WARNINGS**

- · Lamp may shatter and cause injury if broken
- Remove and install by grasping only plastic portion of the lamp.

### **GRAPHS & CHARTS**

**Graphs\_Spectral Power Distribution** 



#### **GENERAL CHARACTERISTICS**

Compact Fluorescent - Plug-Lamp Type

Bulb T4 G24q-1 Base Equivalent Wattage (NOM) 60.0 W

17000.0/20000.0 h Rated Life (NOM)

Starting Temperature (MIN) 0.0 °C Cathode Resistance (NOM) 10.5 Ohm 3.0 mg 198.6755 pg Mercury Content (NOM) Picograms of Mercury (NOM)

Additional Info Dimmable with appropriate

dimming ballast./End of Life Protection (EOL)/TCLP

compliant Facilities:Retail

**Primary Application** Display; Hospitality; Office; Restaurant; Wa

#### PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM) 900.0 Mean Lumens (NOM) 755.0 Nominal Initial Lumens per Watt 69.23077

(NOM)

Color Temperature (NOM) 3500.0 K Color Rendering Index (CRI) 82.0

(NOM)

## **ELECTRICAL CHARACTERISTICS**

Wattage (NOM) 13.0 Voltage (NOM) 91.0 Current (max) (NOM) 5.25 A Open Circuit Voltage (after 190.0 V preheating) (MAX)

Open Circuit Voltage Across

198.0 V

Starter (MIN)

Lamp Current (NOM) 0.175 A Preheat Voltage (MIN) 4.25 V Current Crest Factor (MAX) 1.7 Supply Current Frequency 60.0 Hz

(NOM)

## **DIMENSIONS**

Maximum Overall Length 4.900 in(124.5 mm) (MOL) (NOM) Nominal Length (NOM) 5.000 in(127.0 mm) Base Face to Top of Lamp 4.400 in(111.8 mm) (NOM)

#### **PRODUCT INFORMATION**

**Product Code** 97596 Description

F13DBX/835/ECO4P ANSI Code 60901-IEC-2513-2 **BUNDLE** 

Standard Package

Standard Package GTIN Standard Package Quantity

50 Sales Unit Unit No Of Items Per Sales Unit 1 No Of Items Per Standard 50

Package

**UPC** 043168975964

#### NOTES

- 4-Pin lamp minimum starting temperature is a function of the ballast. Most ballasts are rated with a minimum starting temperature of 50 degrees F (10 C). Ballasts are also available that provide reliable starting to 0 degrees F (-18C) and -20 F (-29C).
- Based on 60Hz reference circuit.
- · Fluorescent lamp lumens decline during life