





GE
Lighting

97604 - F26DBX/E/835/ECO

GE Ecolux® Biax® T4 - Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse



High Color Rendering
Energy Savings



CAUTIONS & WARNINGS

Caution

- Lamp may shatter and cause injury if broken
 - Remove and install by grasping only plastic portion of the lamp.

NOTES

- Based on 60Hz reference circuit.
- Fluorescent lamp lumens decline during life
- This lamp is only recommended for use with single lamp ballasts or parallel wired 2-lamp ballasts

GENERAL CHARACTERISTICS

Lamp Type	Compact Fluorescent - Plug-In
Bulb	T4
Base	G24d-3
Equivalent Wattage (NOM)	100.0 W
Rated Life (NOM)	10000.0 h
Starting Temperature (MIN)	-20.0 °C
Mercury Content (NOM)	3.0 mg
Picograms of Mercury (NOM)	205.4794 pg
Additional Info	TCLP compliant
Primary Application	Facilities;Retail Display;Hospitality;Office;Restaurant;W

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	1710.0
Mean Lumens (NOM)	1460.0
Nominal Initial Lumens per Watt (NOM)	65.76923
Color Temperature (NOM)	3500.0 K
Color Rendering Index (CRI) (NOM)	82.0

ELECTRICAL CHARACTERISTICS

Wattage (NOM)	26.0
Voltage (NOM)	105.0
Lamp Current (NOM)	0.325 A
Current Crest Factor (MAX)	1.7

DIMENSIONS

Maximum Overall Length (MOL) (NOM)	6.670 in(169.4 mm)
Nominal Length (NOM)	6.700 in(170.2 mm)

PRODUCT INFORMATION

Product Code	97604
Description	F26DBX/E/835/ECO
ANSI Code	60901-IEC-0526-2
Standard Package	BUNDLE
Standard Package GTIN	
Standard Package Quantity	50
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	50
UPC	043168976046