

# 97606 - F26DBX/827/ECO

GE Ecolux® Biax® T4 - Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse










# **CAUTIONS & WARNINGS**

- · Lamp may shatter and cause injury if broken
- Remove and install by grasping only plastic portion of the lamp.

#### **GRAPHS & CHARTS**

**Graphs\_Spectral Power Distribution** 



#### **NOTES**

- Based on 60Hz reference circuit.
- · Fluorescent lamp lumens decline during life

#### **GENERAL CHARACTERISTICS**

Lamp Type Compact Fluorescent - Plug-Bulb T4 Base

G24d-3 Equivalent Wattage (NOM) 100.0 W 10000.0 h Rated Life (NOM) Starting Temperature (MIN) -9.0 °C Cathode Resistance (NOM) 2.7 Ohm Mercury Content (NOM) 3.0 mg Picograms of Mercury (NOM) 205.4794 pg Additional Info TCLP compliant **Primary Application** Facilities;Retail

Display; Hospitality; Office; Restaurant; W

## PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM) 1710.0 Mean Lumens (NOM) 1460.0 Nominal Initial Lumens per Watt 65.76923

(NOM)

Color Temperature (NOM) 2700.0 K Color Rendering Index (CRI) 82.0

(NOM)

#### **ELECTRICAL CHARACTERISTICS**

Wattage (NOM) Voltage (NOM) 105.0 Open Circuit Voltage Across 198.0 V Starter (MIN) 0.325 A Lamp Current (NOM) Current Crest Factor (MAX) 1.7

Supply Current Frequency 60.0 Hz

(NOM)

# **DIMENSIONS**

Maximum Overall Length 6.670 in(169.4 mm)

(MOL) (NOM)

Nominal Length (NOM) 6.700 in(170.2 mm) Base Face to Top of Lamp 5.790 in(147.1 mm)

(NOM)

## **PRODUCT INFORMATION**

**Product Code** 97606

F26DBX/827/ECO Description ANSI Code 60901-IEC-0526-2 **BUNDLE** 

Standard Package

Standard Package GTIN

Standard Package Quantity 50 Sales Unit Unit No Of Items Per Sales Unit No Of Items Per Standard 50

Package

**UPC** 043168976060