6/24/2014 Product Details



Product 29728

Number:

Order CF20EL/MICRO/827/RP2

Abbreviation:

**General** 20W Compact Fluorescent Micro Mini **Description:** with integral 120V ballast medium

screw base color temperature 2700K

82CRI

\* Full Case Required

## **Product Information**

Abbrev. With Packaging Info.	CF20ELMICRO827RP2 12/CS 2/SKU
Average Rated Life (hr)	12000

Base Medium
Bulb MICROMINI

Color Rendering Index (CRI) 82

Color Temperature/CCT (K) 2700
Diameter (in) 2.138
Diameter (mm) 54.30

Family Brand Name Dulux® EL

Initial Lumens at 25C 1300

Mean Lumens at 25C 1024

Maximum Overall Length - MOL (in) 4.3

Maximum Overall Length - MOL (mm) 109

6/24/2014 Product Details

Nominal Voltage (V)120.00Nominal Wattage (W)20.00Outside Diameter (in)2Outside Diameter (mm)51.3









## Footnotes

- Approximate initial lumens after 100 hours operation.
- Minimum starting temperature for DULUX EL lamps is 0° F, unless otherwise specified in product literature.
- DULUX ELs meet CSA, FCC and UL requirements.
- Caution: DULUX EL units cannot be used on dimming circuits (unless the lamp is labeled dimmable), emergency exit fixtures or lights, electronic timers, photocells, lighted switches or any other switches that do not meet UL20 Sec. 7.6.15. In outdoor applications, use only in enclosed fixtures to avoid exposure to weather. Use only on 120V, 60 Hz circuits. Never disassemble or modify lamp. Install or remove unit from fixture by grasping plastic base. Best performance achieved when operated at 77degrees F (25 degrees C). 40 Watt lamp is designed for base down orientation only
- The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified conditions and with ballast meeting ANSI specifications. If burning cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature for DULUX EL lamps is 0 degrees F
- Rule of Thumb for Compact Fluorescent Lamps: Divide wattage of incandescent lamp by 4 to determine approximate wattage of compact fluorescent lamp that will provide similar light output.