


17175 - F18BXSPX35RS10PK

GE Biax® T5 - Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse








CAUTIONS & WARNINGS

- · Lamp may shatter and cause injury if broken
- Remove and install by grasping only plastic portion of the lamp.

GRAPHS & CHARTS

Graphs_Spectral Power Distribution



GENERAL CHARACTERISTICS

Lamp Type Compact Fluorescent - Plug-

Bulb

4-Pin (2G11) Base Equivalent Wattage (NOM) 65.0 W 20000.0 h Rated Life (NOM) Starting Temperature (MIN) 10.0 °C Mercury Content (NOM) 4.0 mg 176.9911 pg Picograms of Mercury (NOM) Primary Application Facilities;Retail

Display; Hospitality; Office; Restaurant; Wa

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM) 1250.0 Mean Lumens (NOM) 1130.0 Nominal Initial Lumens per Watt 69.44444 (NOM) Color Temperature (NOM) 3500.0 K Color Rendering Index (CRI) 82.0

ELECTRICAL CHARACTERISTICS

Wattage (NOM) Voltage (NOM) 58.0 Lamp Current (NOM) 0.375 A Current Crest Factor (MAX) 1.7

DIMENSIONS

(NOM)

Maximum Overall Length 10.500 in(266.7 mm) (MOL) (NOM) Nominal Length (NOM) 10.500 in(266.7 mm)

PRODUCT INFORMATION

Product Code 17175

Description F18BXSPX35RS10PK ANSI Code 60901-IEC-2218-2 Standard Package Master

Standard Package GTIN 10043168171752

Standard Package Quantity 40 Sales Unit Unit No Of Items Per Sales Unit No Of Items Per Standard 40

Package

UPC 043168171755

NOTES

- 4-Pin lamp minimum starting temperature is a function of the ballast. Most ballasts are rated with a minimum starting temperature of 50 degrees F (10 C). Ballasts are also available that provide reliable starting to 0 degrees F (-18C) and -20 F (-29C).
- Based on 60Hz reference circuit.
- · Fluorescent lamp lumens decline during life
- Life ratings for the F18BX preheat lamps are based on operating the lamp at 3 hrs per start on a preheat type circuit. Operation on rapid start and instant start ballasts is not recommended. Life ratings for all lamps are based on operating the lamp at 3 hrs per start on a rapid start type ballast. Life rating on a preheat or instant start ballast is 25% lower than other Rapid Start High Lumen Biax.