

22178 - F212D/835/4P

GE 2D® T4 - Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse





CAUTIONS & WARNINGS

Caution

Lamp may shatter and cause injury if broken

- Remove and install by grasping only plastic portion of the lamp.

GENERAL CHARACTERISTICS

Lamp Type

Bulb Base Equivalent Wattage (NOM) Rated Life (NOM) Starting Temperature (MIN) Mercury Content (NOM) Picograms of Mercury (NOM) Primary Application Compact Fluorescent - Plug-In T4 GR10q-4 75.0 W 10000.0 h -4.0 °C 3.0 mg 264.3172 pg Facilities;Retail Display;Hospitality;Office;Restaurant;W

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	1350.0
Mean Lumens (NOM)	1135.0
Nominal Initial Lumens per Watt	64.28571
(NOM)	
Color Temperature (NOM)	3500.0 K
Color Rendering Index (CRI)	82.0
(NOM)	

ELECTRICAL CHARACTERISTICS

Wattage (NOM)21.0Current (max) (NOM)5.25 AOpen Circuit Voltage Across198.0 VStarter (MIN)7Preheat Voltage (MIN)4.25 VCurrent Crest Factor (MAX)1.7

DIMENSIONS

Maximum Overall Length	5.550 in(141.0 mm)
(MOL) (NOM)	
Nominal Length (NOM)	5.500 in(139.7 mm)
Base Face to Top of Lamp	1.070 in(27.2 mm)
(NOM)	

PRODUCT INFORMATION

Product Code Description	22178 F212D/835/4P
Standard Package	Case
Standard Package GTIN	00043168221788
Standard Package Quantity	50
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard	50
Package	
UPC	043168981835

NOTES

• 10-watt, 16-watt and 28-watt 2D lamps may be operated in any position. 21-watt, 38-watt, 39-watt, and 55-watt 2D lamps must be used with the leg market (a) in the diagram below the bend (b), in order to avoid overheating the end of the cap marked (c).

• 4-Pin lamp minimum starting temperature is a function of the ballast. Most ballasts are rated with a minimum starting temperature of 50 degrees F (10 C). Ballasts are also available that provide reliable starting to 0 degrees F (-18C) and -20 F (-29C).

• Based on 60Hz reference circuit.

• Fluorescent lamp lumens decline during life