


## 16952 - F39BXSPX41RS10PK

GE Biax® T5 - Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse





# **CAUTIONS & WARNINGS**

#### Caution

- Lamp may shatter and cause injury if broken
- Remove and install by grasping only plastic portion of the lamp.

## **GENERAL CHARACTERISTICS**

Lamp Type Compact Fluorescent - Plug-

In

Bulb 1

Base 4-Pin (2G11)
Equivalent Wattage (NOM) 180.0 W
Rated Life (NOM) 12000.0 h
Starting Temperature (MIN) 10.0 °C
Mercury Content (NOM) 4.0 mg
Picograms of Mercury (NOM) 132.8021 pg
Primary Application Facilities;Retail

Display; Hospitality; Office; Restaurant; Wa

## PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM) 2850.0
Mean Lumens (NOM) 2510.0
Nominal Initial Lumens per Watt (NOM)
Color Temperature (NOM) 4100.0 K
Color Rendering Index (CRI) 82.0

(NOM)

## **ELECTRICAL CHARACTERISTICS**

 Wattage (NOM)
 39.0

 Voltage (NOM)
 107.0

 Lamp Current (NOM)
 0.428 A

 Current Crest Factor (MAX)
 1.7

#### **DIMENSIONS**

Maximum Overall Length (MOL) (NOM)
Nominal Length (NOM)

16.500 in(419.1 mm)
16.500 in(419.1 mm)

## **PRODUCT INFORMATION**

Product Code 16952

Description F39BXSPX41RS10PK ANSI Code 60901-IEC-4236-1 Standard Package Master

Standard Package GTIN 10043168169520 Standard Package Quantity 40

Standard Package Quantity 40
Sales Unit Unit
No Of Items Per Sales Unit 1
No Of Items Per Standard 40

Package

UPC 043168169523

## NOTES

- 4-Pin lamp minimum starting temperature is a function of the ballast. Most ballasts are rated with a minimum starting temperature of 50 degrees F (10 C). Ballasts are also available that provide reliable starting to 0 degrees F (-18C) and -20 F (-29C).
- Based on 60Hz reference circuit.
- Fluorescent lamp lumens decline during life
- Life ratings for the F18BX preheat lamps are based on operating the lamp at 3 hrs per start on a preheat type circuit. Operation on rapid start and instant start ballasts is not recommended. Life ratings for all lamps are based on operating the lamp at 3 hrs per start on a rapid start type ballast. Life rating on a preheat or instant start ballast is 25% lower than other Rapid Start High Lumen Biax.