6/10/2014 Product Details



Product 20583

Number:

Order FT36DL/841/ECO

Abbreviation:

General DULUX 36W long compact fluorescent lamp with 4-pin base, 4100K

Description: color temperature, 82 CRI, ECOLOGIC for use on magnetic, electronic

and dimming ballasts

Product Information

FT36DL841ECO 10/CS 1/SKU Abbrev. With Packaging Info. Average Rated Life (hr) 12000 2G11 Base Bulb L(T5) 82 Color Rendering Index (CRI) 4100 Color Temperature/CCT (K) 0.000 Diameter (in) Diameter (mm) 0.00 Family Brand Name Dulux® L Industry Standards ANSI C78.901 - 2001 Initial Lumens at 25C 2900 Mean Lumens at 25C 2494 Maximum Overall Length - MOL (in) 16.6 Maximum Overall Length - MOL (mm) 422



Nominal Wattage (W)

Footnotes

36.00

- Approximate initial lumens after 100 hours operation.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.
- There is a NEMA supported, industry issue where T2, T4, and T5 fluorescent and compact fluorescent lamps operated on high frequency ballasts may experience an abnormal end-of-life phenomenon. This end-of-life phenomenon can resultin one or both of the following: 1. Bulb wall cracking near the lamp base. 2. The lamp can overheat in the base area and possibly melt the base and socket. NEMA recommends that high frequency compact fluorescent ballasts have an end-of-life shutdown circuit which will safely and reliably shut down the system in the rare event of an abnormal end-of-life failure mode described above. The final requirements of this system are yet to be defined by ANSI. For additional information refer to NEMA papers on their WEBSITE at www.NEMA.org.
- The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified conditions and with ballast meeting ANSI specifications. If burning cycle is increased, there will be a corresponding increase in the average hours life.

6/10/2014 Product Details

• These lamps may also be operated on rapid start circuits. On rapid start circuits the 24 watt lamp operates at 27 watts and the 36 watt lamp operated at 39 watts. Rated lamp life is unchanged.

• Rule of Thumb for Compact Fluorescent Lamps: Divide wattage of incandescent lamp by 4 to determine approximate wattage of compact fluorescent lamp that will provide similar light output.