

28885 - F17T8XLSPX50ECVG


GE Ecolux® covRguard® Starcoat® T8 - Shatter-Resistant

• Passes TCLP, which can lower disposal costs.









CAUTIONS & WARNINGS

Caution

- · Lamp may shatter and cause injury if broken
- Wear safety glasses and gloves when handling lamp.
- Do not use excessive force when installing lamp.

Warning

- · Risk of Electric Shock
- Turn power off before inspection, installation or removal.

GRAPHS & CHARTS

Graphs_Lamp Mortality

GENERAL CHARACTERISTICS

Linear Fluorescent - Straight Lamp Type

Linear

Bulb

Base Medium Bi-Pin (G13) Rated Life (NOM) 40000.0 h Rated Life (instant start) @ 18000 h @ 3 h 24000 h @ 12 h

Rated Life (rapid start) @ Time 40000.0 @ 3.0/45000.0 @

12.0 h

Bulb Material Soda lime Starting Temperature (MIN) 10.0 °C Mercury Content (NOM) 2.95 mg 98.8871 pg Picograms of Mercury (NOM) Additional Info TCLP compliant

Primary Application Shatter-Resistant; Speciality

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM) 1310.0 Mean Lumens (NOM) 1243.0 Nominal Initial Lumens per Watt 77.05882

(NOM)

Color Temperature (NOM) 5000.0 K Color Rendering Index (CRI) 82.0

(NOM)

ELECTRICAL CHARACTERISTICS

Wattage (NOM) 17.0 Open Circuit Voltage (rapid 285.0 V start) (MAX)

Cathode Resistance Ratio - Rh/ 4.25

Rc (MIN)

Cathode Resistance Ratio - Rh/ 6.5

Rc (MAX)

Current Crest Factor (MAX) 1.7

DIMENSIONS

Maximum Overall Length 23.780 in(604.0 mm)

(MOL) (NOM)

Minimum Overall Length (NOM) 23.670 in(601.2 mm) Nominal Length (NOM) 24.000 in(609.6 mm) Bulb Diameter (DIA) (MIN) 0.940 in(23.9 mm) Bulb Diameter (DIA) (MAX) 1.100 in(27.9 mm) Bulb Diameter (DIA) (NOM) 1.000 in(25.4 mm) Max Base Face to Base Face 23.220 in(589.8 mm)

(A) (NOM)

Face to End of Opposing Pin 23.400 in(594.4 mm)

(B) (MIN)

Face to End of Opposing Pin 23.500 in(596.9 mm) (B) (MAX)

End of Base Pin to End of

23.670 in(601.2 mm)

Opposite Pin End (C) (NOM)

PRODUCT INFORMATION

Product Code 28885

F17T8XLSPX50ECVG Description

Standard Package Case

Standard Package GTIN 10043168288856


Standard Package Quantity 24 Sales Unit Unit No Of Items Per Sales Unit No Of Items Per Standard 24

Package

UPC 043168288859



Graphs_Lumen Maintenance



Graphs_Spectral Power Distribution

