



**Product** 20731

**Number:**

**Order** FPC40/830

**Abbreviation:**

**General** 40W, T5 Pentron Circline fluorescent lamp, 3000K

**Description:** color temperature, rare earth phosphor, 82 CRI

### Product Information

Abbrev. With Packaging Info.	FPC40830 12/CS 1/SKU
Actual Length (in)	12.008
Actual Length (mm)	305.00
Average Rated Life (hr)	12000
Base	2GX13
Bulb	T5
Color Rendering Index (CRI)	80
Color Temperature/CCT (K)	3000
Diameter (in)	0.630
Diameter (mm)	16.00
Family Brand Name	Pentron®
Initial Lumens at 25C	3400
Mean Lumens at 25C	2815
Nominal Length (in)	12.008
Nominal Length (mm)	305.00
Nominal Wattage (W)	40.00
Outside Diameter (in)	11.54 - 12.01
Outside Diameter (mm)	293-305



### Footnotes

- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified conditions and with ballast meeting ANSI specifications. If burning cycle is increased, there will be a corresponding increase in the average hours life.
- Lumen output and life rated on high frequency operation.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.
- There is a NEMA supported, industry issue where T2, T4, and T5 fluorescent and compact fluorescent lamps operated on high frequency ballasts may experience an abnormal end-of-life phenomenon. This end-of-life phenomenon can result in one or both of the following: 1. Bulb wall cracking near the lamp base. 2. The lamp can overheat in the base area and possibly melt the base and socket. NEMA recommends that high frequency compact fluorescent ballasts have an end-of-life shutdown circuit which will safely and reliably shut down the system in the rare event of an abnormal end-of-life failure mode described above. The final requirements of this

system are yet to be defined by ANSI. For additional information refer to NEMA papers on their WEBSITE at [www.NEMA.org](http://www.NEMA.org).