

**Product** 21525**Number:****Order** F18T12/350BL/700/PH**Abbreviation:****General** 32W T12 preheat fluorescent lamp, Blacklight phosphor
Description: (356 nm), 700 mA

Product Information

Abbrev. With Packaging Info.	F18T12350BL700PH 30/CS 1/SKU
Base	Medium Bipin
Bulb	T12
Nominal Wattage (W)	32.00

Footnotes

- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified conditions and with ballast meeting ANSI specifications. If burning cycle is increased, there will be a corresponding increase in the average hours life.
- Starter required.
- These lamps are not intended and should not be used for diagnostic, therapeutic, or cosmetic purposes.
- CAUTION: This lamp emits ultraviolet (UV) power during operation and is in Risk Group 2 per ANSI/IESNA RP-27.3-96. Exposure at less than 0.8 meters (31 inches) should be limited; for example exposure at 0.55m (22 inches) should not exceed 4 hours in an 8 hour interval (see ANSI/IESNA RP-27.1-96). Certain medications and chemicals can increase an individual's sensitivity. Consult your physician for specific information. Protective eyewear should be worn in occupational situations involving long term exposure in close proximity to the lamp. This lamp is not intended and should not be used for diagnostic, therapeutic or cosmetic purposes.