



GE
Lighting

71637 - F21T5/830/WM/ECO

GE Ecolux® Watt-Miser® Starcoat® T5

- Saves energy compared to standard wattage lamps
- Passes TCLP, which can lower disposal costs.



High Color Rendering



GENERAL CHARACTERISTICS

Lamp Type	Linear Fluorescent - Straight Linear
Bulb	T5
Base	Miniature Bi-Pin (G5)
Rated Life (NOM)	25000.0 h
Rated Life (rapid start) @ Time	25000.0 @ 3.0/30000.0 @ 12.0 h
Bulb Material	Soda lime
Starting Temperature (MIN)	-20.0 °C
Mercury Content (NOM)	2.5 mg
Picograms of Mercury (NOM)	51.8 pg
Additional Info	Dimmable with appropriate dimming ballast./TCLP compliant
Primary Application	Energy Saving

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	2100.0
Mean Lumens (NOM)	1930.0
Nominal Initial Lumens per Watt (NOM)	105.0
Color Temperature (NOM)	3000.0 K
Color Rendering Index (CRI) (NOM)	85.0
S/P Ratio (Scotopic/Photopic Ratio) (NOM)	1.3

ELECTRICAL CHARACTERISTICS




Wattage (NOM)	20.0
Cathode Resistance Ratio - Rh/Rc (MIN)	4.25
Cathode Resistance Ratio - Rh/Rc (MAX)	6.5
Current Crest Factor (MAX)	1.7


DIMENSIONS

Maximum Overall Length (MOL) (NOM)	33.400 in(848.4 mm)
Nominal Length (NOM)	33.400 in(848.4 mm)
Bulb Diameter (DIA) (MAX)	0.670 in(17.0 mm)
Bulb Diameter (DIA) (NOM)	0.625 in(15.9 mm)
Max Base Face to Base Face (A) (NOM)	33.430 in(849.1 mm)
Face to End of Opposing Pin (B) (MIN)	33.610 in(853.7 mm)
Face to End of Opposing Pin (B) (MAX)	33.700 in(856.0 mm)

PRODUCT INFORMATION

Product Code	71637
Description	F21T5/830/WM/ECO
Standard Package	Case
Standard Package GTIN	10043168716373
Standard Package Quantity	40
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	40
UPC	043168716376





GRAPHS & CHARTS

Graphs_Spectral Power Distribution

