

## 97627 - F18TBX/841/A/ECO

GE Ecolux® Biax® T4 - Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse



Photo Not Available

Photo Not Available





## **CAUTIONS & WARNINGS**

#### Caution

- Lamp may shatter and cause injury if broken
- Remove and install by grasping only plastic portion of the lamp.

#### **GENERAL CHARACTERISTICS**

Lamp Type Compact Fluorescent - Plug-

Bulb T4
Base GX24q-2
Equivalent Wattage (NOM) 65.0 W
Rated Life (NOM) 17000.0 h
Starting Temperature (MIN) 0.0 °C
Cathode Resistance (NOM) 6.05 Ohm
Mercury Content (NOM) 3.0 mg

Picograms of Mercury (NOM) 173.0104 pg Rated Life (rapid start) @ Time 12000.0 @ 3.0/20000.0 @

12.0 h

Additional Info Dimmable with appropriate

dimming ballast./End of Life Protection (EOL)/TCLP

compliant

Primary Application Facilities; Retail

Display;Hospitality;Office;Restaurant;W

#### **PHOTOMETRIC CHARACTERISTICS**

Initial Lumens (NOM) 1200.0 Mean Lumens (NOM) 1020.0 Nominal Initial Lumens per Watt 66.66667

(NOM)

Color Temperature (NOM) 4100.0 K Color Rendering Index (CRI) 82.0

(NOM)

## **ELECTRICAL CHARACTERISTICS**

 Wattage (NOM)
 18.0

 Voltage (NOM)
 120.0

 Current (max) (NOM)
 5.25 A

 Open Circuit Voltage (after
 250.0 V

preheating) (MAX)

Open Circuit Voltage Across 198.0 V

Starter (MIN)

Lamp Current (NOM) 0.225 A
Preheat Voltage (MIN) 4.25 V
Current Crest Factor (MAX) 1.7
Supply Current Frequency 60.0 Hz

(NOM)

# **DIMENSIONS**

Maximum Overall Length 4.800 in(121.9 mm)

(MOL) (NOM)

Nominal Length (NOM) 4.800 in(121.9 mm) Base Face to Top of Lamp 4.250 in(107.9 mm)

(NOM)

# **PRODUCT INFORMATION**

Product Code 97627

Description F18TBX/841/A/ECO ANSI Code 60901-IEC-3418-1

Standard Package Case

Standard Package GTIN 10043168976272

Standard Package Quantity 10
Sales Unit Unit
No Of Items Per Sales Unit 1
No Of Items Per Standard 10

Package

UPC 043168976275

## NOTES

- 4-Pin lamp minimum starting temperature is a function of the ballast. Most ballasts are rated with a minimum starting temperature of 50 degrees F (10 C). Ballasts are also available that provide reliable starting to 0 degrees F (-18C) and -20 F (-29C).
- Amalgam product experience stable brightness over a wider temperature range and in various operating positions.
- Based on 60Hz reference circuit.
- Fluorescent lamp lumens decline during life