

**Product** 25322**Number:****Order** F30T12/CW/HO**Abbreviation:**

**General** 42W, 30" MOL, T12 HO (800 mA) rapid start fluorescent  
**Description:** lamp, Cool White phosphor, 4200K color temperature, 60 CRI

**\* Full Case Required****Product Information**

Abbrev. With Packaging Info.	F30T12CWHO 30/CS 1/SKU
Actual Length (in)	27.909
Actual Length (mm)	708.89
Average Rated Life (hr)	9000
Base	Recessed Double Contact
Bulb	T12
Color Rendering Index (CRI)	60
Color Temperature/CCT (K)	4200
Diameter (in)	1.593
Diameter (mm)	40.46
Industry Standards	ANSI C78.81 - 2001
Initial Lumens at 25C	2250
Mean Lumens at 25C	1825
Mean Lumens at 35C	1825
Nominal Length (in)	36.000
Nominal Length (mm)	914.40
Nominal Wattage (W)	42.00

**Footnotes**

- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified conditions and with ballast meeting ANSI specifications. If burning cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.