

### 27617 - F32T8/XL/SP35ECO

#### GE Ecolux® Starcoat® T8

- Passes TCLP, which can lower disposal costs.
- Provides significantly longer life than standard lamp helping to reduce maintenance costs

## Photo Not Available

High Color

Rendering

Meets Federal Minimum Efficiency Standards

Photo Not Available





#### **CAUTIONS & WARNINGS**

- . Lamp may shatter and cause injury if broken
- Wear safety glasses and gloves when handling lamp.
- Do not use excessive force when installing lamp.

- Risk of Electric Shock
- Turn power off before inspection, installation or removal.

#### **GRAPHS & CHARTS**

**Graphs\_Spectral Power Distribution** 

#### **GENERAL CHARACTERISTICS**

Lamp Type Linear Fluorescent - Straight

Linear

Bulb

Base Medium Bi-Pin (G13) Rated Life (NOM) 40000.0 h Rated Life (instant start) @ 25000 h @ 3 h 36000 h @ 12 h

Rated Life (rapid start) @ Time 40000.0 @ 3.0/45000.0 @

12.0 h

1.4

**Bulb Material** Soda lime Starting Temperature (MIN) 10.0 °C Mercury Content (NOM) 2.95 mg 27.3 pg Picograms of Mercury (NOM) Additional Info TCLP compliant **Primary Application** Full Wattage

#### PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM) 2800.0 Mean Lumens (NOM) 2660.0 Nominal Initial Lumens per Watt 87.5

(NOM)

Color Temperature (NOM) 3500.0 K Color Rendering Index (CRI) 78.0

(NOM)

S/P Ratio (Scotopic/Photopic

Ratio) (NOM)

#### **ELECTRICAL CHARACTERISTICS**

Wattage (NOM)

Open Circuit Voltage (rapid 315 V @ 10 °C

start) Min @ Temperature

Cathode Resistance Ratio - Rh/ 4.25

Rc (MIN)

Cathode Resistance Ratio - Rh/ 6.5

Rc (MAX)

Current Crest Factor (MAX) 1.7

### **DIMENSIONS**

Maximum Overall Length 48.000 in(1219.2 mm)

(MOL) (NOM)

Minimum Overall Length (NOM) 47.670 in(1210.8 mm) Nominal Length (NOM) 48.000 in(1219.2 mm) Bulb Diameter (DIA) (MIN) 0.940 in(23.9 mm) Bulb Diameter (DIA) (MAX) 1.100 in(27.9 mm) Bulb Diameter (DIA) (NOM) 1.000 in(25.4 mm) Max Base Face to Base Face 47.220 in(1199.4 mm)

(A) (NOM)

Face to End of Opposing Pin 47.400 in(1204.0 mm)

(B) (MIN)

Face to End of Opposing Pin

(B) (MAX)

End of Base Pin to End of Opposite Pin End (C) (NOM) 47.500 in(1206.5 mm) 47.670 in(1210.8 mm)

## **PRODUCT INFORMATION**

Product Code 27617

Description F32T8/XL/SP35ECO

ANSI Code 1005-2 Standard Package Case

Standard Package GTIN 10043168276174

Standard Package Quantity 36 Sales Unit Unit

No Of Items Per Sales Unit 1 36

No Of Items Per Standard

Package

**UPC** 043168276177

# Photo Not Available

**Graphs\_Lumen Maintenance** 

# Photo Not Available

**Graphs\_Lamp Mortality** 

Photo Not Available