

Product 24599**Number:****Order** F34/DX/SS (F40/DX/SS)**Abbreviation:**

General 34W, T12 rapid start SUPER SAVER fluorescent lamp,
Description: Daylight Deluxe phosphor, 6500K color temperature, 88 CRI, replaces F40T12 RS lamps. 20000 Avg rated life at 3 hrs/start, 28800 Avg rated life at 12 hrs/start

*** Full Case Required****Product Information**

Abbrev. With Packaging Info.	F34DXSS (F40DXSS) 30/CS 1/SKU
Actual Length (in)	47.780
Actual Length (mm)	1213.61
Average Rated Life (hr)	20000
Base	Medium Bip in
Bulb	T12
Color Rendering Index (CRI)	88
Color Temperature/CCT (K)	6500
Diameter (in)	1.591
Diameter (mm)	40.40
Family Brand Name	SuperSaver®
Industry Standards	ANSI C78.81 - 2001
Initial Lumens at 25C	1930
Mean Lumens at 25C	1565
Nominal Length (in)	48.000
Nominal Length (mm)	1219.20
Nominal Wattage (W)	34.00

**Footnotes**

- Average life rating at 12 hours operation per start is 28,800 hours.
- Recommended for use on one or two lamp 40 watt rapid start, high power factor, lead, indoor ballasts that meet ANSI standards. Not intended for use: (1) at lamp ambient temperatures below 60 degrees F or in drafty locations, (2) on low power factor ballasts, (3) reduced current/reduced light output ballasts, (4) dimming ballasts, or (5) on inverter operated emergency lighting systems unless any of the above equipment is specifically listed for use with 34 watt lamps.
- Average rated life is measured at 3 hours per start on 2-lamp, rapid start magnetic ballasts per IES recommended practice. Lamp life on single-lamp rapid start ballasts may be reduced.
- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified conditions and with ballast meeting ANSI specifications. If burning cycle is increased, there will be a corresponding increase in the average hours life.
- The "RS" designation has been eliminated to simplify the ordering abbreviation.

