

**Product** 24829**Number:****Order** F48T12/D35/SS**Abbreviation:**

**General** 32W, 48" MOL, T12 instant start Slimline SUPER SAVER  
**Description:** fluorescent lamp, Designer rare earth phosphor, 3500K color temperature, 70 CRI

**\* Full Case Required****Product Information**

Abbrev. With Packaging Info.	F48T12D35SS 30/CS 1/SKU
Actual Length (in)	46.000
Actual Length (mm)	1168.40
Average Rated Life (hr)	9000
Base	Single Pin
Bulb	T12
Color Rendering Index (CRI)	70
Color Temperature/CCT (K)	3500
Diameter (in)	1.593
Diameter (mm)	40.46
Family Brand Name	Designer, SuperSaver
Industry Standards	ANSI C78.81 - 2001
Initial Lumens at 25C	2575
Mean Lumens at 25C	2369
Mean Lumens at 35C	2369
Nominal Length (in)	48.000
Nominal Length (mm)	1219.20
Nominal Wattage (W)	32.00

**Footnotes**

- Recommended for use on one or two lamp high power factor, lead, instant-start, indoor ballasts that meet ANSI standards. Not intended for use: (1) at lamp ambient temperatures below 60 degrees F or in drafty locations, (2) on low power factor ballasts, (3) reduced current/reduced light output ballasts, (4) dimming ballasts, or (5) on inverter operated emergency lighting systems unless any of the above equipment is specifically listed for use with 32 watt or 60 watt lamps.
- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified conditions and with ballast meeting ANSI specifications. If burning cycle is increased, there will be a corresponding increase in the average hours life.