

46727 - F35W/T5/835/ECO

GE Ecolux® Starcoat® T5


• Passes TCLP, which can lower disposal costs.

a product of

ecomagination







CAUTIONS & WARNINGS

Caution


- Lamp may shatter and cause injury if broken
- Wear safety glasses and gloves when handling lamp.
- Do not use excessive force when installing lamp.

Warning


- Risk of Electric Shock
- Turn power off before inspection, installation or removal.

GRAPHS & CHARTS

Graphs_Lumen Maintenance



Graphs_Lamp Mortality



GENERAL CHARACTERISTICS

Lamp Type Linear Fluorescent - Straight

Linear

Bulb T5

Base Miniature Bi-Pin (G5)

Rated Life (NOM) 30000.0 h

Rated Life (rapid start) @ Time 30000.0 @ 3.0/36000.0 @

12.0 h Soda lime

1.5

Bulb Material Soda lime
Starting Temperature (MIN) -20.0 °C
Mercury Content (NOM) 2.5 mg
Picograms of Mercury (NOM) 24.9 pg
Additional Info TCLP compliant
Primary Application Full Wattage

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM) 3650.0 Mean Lumens (NOM) 3350.0 Nominal Initial Lumens per Watt 104.2857

(NOM)

Color Temperature (NOM) 3500.0 K Color Rendering Index (CRI) 85.0

(NOM)

S/P Ratio (Scotopic/Photopic

Ratio) (NOM)

ELECTRICAL CHARACTERISTICS

Wattage (NOM) 35.0

Open Circuit Voltage (rapid 530 V @ 10 °C

start) Min @ Temperature Cathode Resistance Ratio - Rh/ 4.25

Rc (MIN)

Cathode Resistance Ratio - Rh/ 6.5

Rc (MAX)

Current Crest Factor (MAX) 1.7

DIMENSIONS

Maximum Overall Length 57.100 in(1450.3 mm)

(MOL) (NOM)

 Nominal Length (NOM)
 57.100 in(1450.3 mm)

 Bulb Diameter (DIA) (MAX)
 0.670 in(17.0 mm)

 Bulb Diameter (DIA) (NOM)
 0.625 in(15.9 mm)

 Max Base Face to Base Face
 57.050 in(1449.1 mm)

(A) (NOM)

Face to End of Opposing Pin 57.230 in(1453.6 mm)

(B) (MIN)

Face to End of Opposing Pin 57.330 in(1456.2 mm)

(B) (MAX)

) (MAX)

Product Code 46727

PRODUCT INFORMATION

Description F35W/T5/835/ECO

Standard Package Case

Standard Package GTIN 10043168467275

Standard Package Quantity 40 Sales Unit Unit

No Of Items Per Sales Unit 1 No Of Items Per Standard 40

Package

UPC 043168467278

Graphs_Spectral Power Distribution

