



90519 - 48PAR/HIR+/FL25

GE HIR™ PLUS PAR38

• Up to 42% more efficient than standard halogen Up to 27% energy savings









CAUTIONS & WARNINGS

Caution

- Lamp may shatter and cause injury if broken
- Do not use lamp if outer glass is scratched or broken.
- Risk of Burn
- Allow lamp to cool before handling.

Warning

- Risk of Fire
- Keep combustible materials away from lamp. Risk of Electric Shock
- Turn power off before inspection, installation or removal.
- Unexpected lamp rupture may cause injury, fire, or property damage
- Do not use lamp if outer glass is scratched or broken.

GENERAL CHARACTERISTICS

Lamp Type Bulb Base Filament Rated Life (NOM) Life in Years (NOM) **Primary Application**

Halogen - PAR PAR38 Medium Skirt (E26/50x39) CC-8 4200.0 h 3.8 Indoor and outdoor Floodlight

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM) 970.0 Center Beam Candlepower 3800.0 (CBCP) (NOM) Color Temperature (NOM) 2750.0 K Beam Spread (NOM) 25.0 ° Nominal Initial Lumens per Watt (NOM)

20.20833

ELECTRICAL CHARACTERISTICS

Wattage (NOM) 48.0 Voltage (NOM) 120.0 Estimated Energy Cost per 5.78 Year (NOM)

DIMENSIONS

Product Code

Maximum Overall Length (MOL) (NOM) Bulb Diameter (DIA) (NOM)

PRODUCT INFORMATI

)	4.750 in(120.6 mm)
ON	
	90519
	48PAR/HIR+/FL25
	Case
	4004040005407

Description Standard Package Standard Package GTIN Standard Package Quantity Sales Unit No Of Items Per Sales Unit No Of Items Per Standard Package UPC

10043168905197 12 Unit 1 12

5.313 in(135.0 mm)

043168905190