

**Product** 20804**Number:****Order** L70W / 21 - 840**Abbreviation:****General** 70" MOL, T8 preheat fluorescent lamp, 4000K color**Description:** temperature rare earth phosphor, 80 CRI, typically used in refrigeration equipment. 15000 Avg rated life at 3 hrs/start*** Full Case Required****Product Information**

Abbrev. With Packaging Info.	L70W21840 25/CS 1/SKU
Actual Length (in)	70.000
Actual Length (mm)	1778.00
Average Rated Life (hr)	15000
Base	Medium Bip in
Bulb	T8
Color Rendering Index (CRI)	80
Color Temperature/CCT (K)	4000
Diameter (in)	0.000
Diameter (mm)	0.00
Initial Lumens at 25C	6550
Mean Lumens at 25C	6026
Nominal Length (in)	70.000
Nominal Length (mm)	1778.00
Nominal Wattage (W)	70.00

**Footnotes**

- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified conditions and with ballast meeting ANSI specifications. If burning cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.