

**Product** 25171**Number:****Order** F72T12/CW/HO/ECO**Abbreviation:****General** 85W, 72" MOL, T12 HO (800 mA) rapid start fluorescent lamp, Cool**Description:** White phosphor, 4200K color temperature, 60 CRI, ECOLOGIC*** Full Case Required****Product Information**

Abbrev. With Packaging Info.	F72T12CWHOECO 117V 15/CS 1/SKU
Actual Length (in)	69.886
Actual Length (mm)	1775.10
Average Rated Life (hr)	12000
Base	Recessed Double Contact
Bulb	T12
Color Rendering Index (CRI)	60
Color Temperature/CCT (K)	4200
Diameter (in)	1.593
Diameter (mm)	40.46
Family Brand Name	Ecologic®
Industry Standards	ANSI C78.81 - 2001
Initial Lumens at 25C	6250
Mean Lumens at 25C	5063
Mean Lumens at 35C	5063
Nominal Length (in)	72.000
Nominal Length (mm)	1828.80
Nominal Voltage (V)	117.00
Nominal Wattage (W)	85.00

**Footnotes**

- May be operated at 100 watts (1000MA) same as F84T12/HO.
- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified conditions and with ballast meeting ANSI specifications. If burning cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.
- SYLVANIA ECOLOGIC fluorescent lamps are designed to pass the Federal Toxic Characteristic Leaching Procedure (TCLP) criteria for classification as non-hazardous waste in most states. TCLP test results are available upon request. Lamp disposal regulations may

vary, check your local & state regulations. For more information, please visit www.lamprecycle.org