6/10/2014 Product Details



Product 27250

Number:

Order F72T12/D35

Abbreviation:

General 55W, 72" MOL, T12 instant start Slimline fluorescent lamp,

Description: Designer rare earth phosphor, 3500K color temperature, 70

CRI

Product Information

Designer

Abbrev. With Packaging Info. F72T12D35 15/CS 1/SKU

Actual Length (in) 70.000 Actual Length (mm) 1778.00 Average Rated Life (hr) 12000 Base Single Pin Bulb T12 70 Color Rendering Index (CRI) 3500 Color Temperature/CCT (K) Diameter (in) 1.593 40.46 Diameter (mm)

Industry Standards ANSI C78.81 - 2001

 Initial Lumens at 25C
 4700

 Mean Lumens at 25C
 4324

 Mean Lumens at 35C
 4324

 Nominal Length (in)
 72.000

 Nominal Length (mm)
 1828.80

 Nominal Wattage (W)
 55.00



Family Brand Name

Footnotes

- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified conditions and with ballast meeting ANSI specifications. If burning cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.
- Average life rating at 12 hours operation per start is 18,000 hours.