



Product 27255

Number:

Order F72T12/D830

Abbreviation:

General 55W, 72" MOL, T12 instant start Slimline fluorescent lamp,
Description: Designer rare earth phosphor, 3000K color temperature, 80 CRI

Product Information

Abbrev. With Packaging Info.	F72T12D830 15/CS 1/SKU
Actual Length (in)	70.000
Actual Length (mm)	1778.00
Average Rated Life (hr)	12000
Base	Single Pin
Bulb	T12
Color Rendering Index (CRI)	80
Color Temperature/CCT (K)	3000
Diameter (in)	1.593
Diameter (mm)	40.46
Family Brand Name	Designer 800
Industry Standards	ANSI C78.81 - 2001
Initial Lumens at 25C	4800
Mean Lumens at 25C	4512
Mean Lumens at 35C	4512
Nominal Length (in)	72.000
Nominal Length (mm)	1828.80
Nominal Wattage (W)	55.00



Footnotes

- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified conditions and with ballast meeting ANSI specifications. If burning cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.
- Average life rating at 12 hours operation per start is 18,000 hours.