



**Product** 27256  
**Number:**

**Order** F72T12/CW  
**Abbreviation:**

**General** 55W, 72" MOL, T12 instant start Slimline fluorescent lamp,  
**Description:** Cool White phosphor, 4200K color temperature, 60 CRI

**\* Full Case Required**

**Product Information**

Abbrev. With Packaging Info.	F72T12CW 15/CS 1/SKU
Actual Length (in)	70.000
Actual Length (mm)	1778.00
Average Rated Life (hr)	12000
Base	Single Pin
Bulb	T12
Color Rendering Index (CRI)	60
Color Temperature/CCT (K)	4200
Diameter (in)	1.593
Diameter (mm)	40.46
Industry Standards	ANSI C78.81 - 2001
Initial Lumens at 25C	4500
Mean Lumens at 25C	3960
Mean Lumens at 35C	3960
Nominal Length (in)	72.000
Nominal Length (mm)	1828.80
Nominal Wattage (W)	55.00

**Footnotes**

- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified conditions and with ballast meeting ANSI specifications. If burning cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.
- Average life rating at 12 hours operation per start is 18,000 hours.