


14201 - F96T12SP30WM15PK


GE Watt-Miser® T12

Saves energy compared to standard wattage lamps



Reduced Wattage Meets Federal Minimum Efficiency Standards





CAUTIONS & WARNINGS

Caution

Lamp may shatter and cause injury if broken


- Wear safety glasses and gloves when handling lamp.

- Do not use excessive force when installing lamp.

Warning

- Risk of Electric Shock
- Turn power off before inspection, installation or removal.

GRAPHS & CHARTS



Wavelength (nm)

Graphs_Lumen Maintenance

GENERAL CHARACTERISTICS

Lamp Type

Bulb Base Rated Life (NOM) Bulb Material Starting Temperature (MIN) Mercury Content (NOM) Picograms of Mercury (NOM) Primary Application Linear Fluorescent - Straight Linear T12 Single Pin (Fa8) 12000.0 h Soda lime 15.0 °C 15.0 mg 233.2 pg Energy Saving

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)5700.0Mean Lumens (NOM)5360.0Nominal Initial Lumens per Watt95.0(NOM)Color Temperature (NOM)3000.0 KColor Rendering Index (CRI)70.0(NOM)Color Rendering Index (CRI)70.0

ELECTRICAL CHARACTERISTICS

Wattage (NOM)60.0Open Circuit Voltage (rapid565 V @ 10 °Cstart) Min @ TemperatureCathode Resistance Ratio - Rh/Cathode Resistance Ratio - Rh/4.25Rc (MIN)Cathode Resistance Ratio - Rh/Cathode Resistance Ratio - Rh/6.5Rc (MAX)1.7

DIMENSIONS

Maximum Overall Length (MOL) (NOM) Minimum Overall Length (NOM) Nominal Length (NOM) Bulb Diameter (DIA) (MIN) Bulb Diameter (DIA) (MAX) Bulb Diameter (DIA) (NOM) Max Base Face to Base Face (A) (NOM) Face to End of Opposing Pin (B) (MIN) Face to End of Opposing Pin (B) (MAX) End of Base Pin to End of Opposite Pin End (C) (NOM) 96.000 in(2438.4 mm)

96.0	(40 in(2381.0 mm) (00 in(2438.4 mm)
1.59	0 in(35.8 mm) 00 in(40.4 mm) 00 in(38.1 mm)
93.3	in(2369.8 mm)
	20 in(2372.9 mm) 50 in(2378.7 mm)
35.0	50 m(2570.7 mm)

PRODUCT INFORMATION

Product Code Description ANSI Code Standard Package Standard Package GTIN Standard Package Quantity Sales Unit No Of Items Per Sales Unit No Of Items Per Standard Package UPC

14201 F96T12SP30WM15PK 3006-1 Case 10043168142011 15 Unit 1 15

93.740 in(2381.0 mm)

043168142014

