6/10/2014 Product Details



Product 22148

**Number:** 

Order FO96/835/ECO

Abbreviation:

General 59W, 96" MOL, T8 OCTRON fluorescent lamp, 3500K color

**Description:** temperature, rare earth phosphor, 82 CRI, suitable for IS operation,

**ECOLOGIC** 

\* Full Case Required

## **Product Information**

Abbrev. With Packaging Info. FO96835ECO 24/CS 1/SKU

Actual Length (in) 94.000
Actual Length (mm) 2387.60
Average Rated Life (hr) 15000
Base Single Pin
Bulb T8
Color Rendering Index (CRI) 82
Color Temperature/CCT (K) 3500

Color Rendering Index (CRI) 82
Color Temperature/CCT (K) 3500
Diameter (in) 1.096
Diameter (mm) 27.84

Family Brand Name Octron® 800, Ecologic Industry Standards ANSI C78.81 - 2001

Initial Lumens at 25C 5900 Mean Lumens at 25C 5428 Mean Lumens at 35C 5428 Nominal Length (in) 96.000 Nominal Length (mm) 2438.40 Nominal Wattage (W) 59.00 Life at 3 hrs./start on IS ballasts 18000 Life at 12 hrs./start on IS ballasts 24000



## **Footnotes**

- The lumen maintenance factor used to determine the mean lumens value was 92%, measured at 40% of the average rated life, 15,000 hours. The lumen maintenance factor at 4,000-4,800 hours (for comparison to F96T12 HO and F96T12 Slimline instant start lamps) is 93%.
- Approximate initial lumens after 100 hours operation.

6/10/2014 Product Details

- The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified conditions and with ballast meeting ANSI specifications. If burning cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.
- SYLVANIA ECOLOGIC fluorescent lamps are designed to pass the Federal Toxic Characteristic Leaching Procedure (TCLP) criteria for classification as non-hazardous waste in most states. TCLP test results are available upon request. Lamp disposal regulations may vary, check your local & state regulations. For more information, please visit www.lamprecycle.org