

**Product** 25296**Number:****Order** F96T12/CW/VHO/SS**Abbreviation:****General** 195W, 96" MOL T12 VHO (1500 mA) rapid start**Description:** fluorescent lamp, Cool White phosphor, 4200K color temperature, 60 CRI**\* Full Case Required****Product Information**

Abbrev. With Packaging Info.	F96T12CWVHOSS 15/CS 1/SKU
Actual Length (in)	93.909
Actual Length (mm)	2385.29
Average Rated Life (hr)	10000
Base	Recessed Double Contact
Bulb	T12
Color Rendering Index (CRI)	60
Color Temperature/CCT (K)	4200
Diameter (in)	1.593
Diameter (mm)	40.46
Family Brand Name	VHO
Initial Lumens at 25C	13000
Mean Lumens at 35C	9100
Nominal Length (in)	96.000
Nominal Length (mm)	2438.40
Nominal Wattage (W)	195.00

**Footnotes**

- Recommended for use on 2-lamp high power factor, lead, 8-foot lamp, very high output, indoor ballasts that meet ANSI standards. Not intended for use: (1) at lamp ambient temperatures below 60 degrees F or in drafty locations, (2) on low power factor ballasts, (3) reduced current/reduced light output ballasts, (4) dimming ballasts, or (5) on inverter operated emergency lighting systems unless equipment is specifically listed for use with 195 watt lamps.
- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified conditions and with ballast meeting ANSI specifications. If burning cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.
- Average life rating at 12 hours operation per start is 15,000 hours.