

Product 29828**Number:****Order** F96T12/DX/SS**Abbreviation:****General** 60W, 96" MOL, T12 instant start Slimline SUPER SAVER fluorescent lamp, Daylight phosphor, 6500K color**Description:** temperature, 88 CRI, replaces F96T12 IS lamps*** Full Case Required****Product Information**

Abbrev. With Packaging Info.	F96T12DXSS 15/CS 1/SKU
Actual Length (in)	94.000
Actual Length (mm)	2387.60
Average Rated Life (hr)	12000
Base	Single Pin
Bulb	T12
Color Rendering Index (CRI)	88
Color Temperature/CCT (K)	6500
Diameter (in)	1.593
Diameter (mm)	40.46
Family Brand Name	SuperSaver®
Initial Lumens at 25C	3860
Mean Lumens at 35C	3397
Nominal Length (in)	96.000
Nominal Length (mm)	2438.40
Nominal Wattage (W)	60.00

**Footnotes**

- Recommended for use on one or two lamp high power factor, lead, instant-start, indoor ballasts that meet ANSI standards. Not intended for use: (1) at lamp ambient temperatures below 60 degrees F or in drafty locations, (2) on low power factor ballasts, (3) reduced current/reduced light output ballasts, (4) dimming ballasts, or (5) on inverter operated emergency lighting systems unless any of the above equipment is specifically listed for use with 32 watt or 60 watt lamps.
- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified conditions and with ballast meeting ANSI specifications. If burning cycle is increased, there will be a corresponding increase in the average hours life.
- Average life rating at 12 hours operation per start is 18,000 hours.