

**Product** 64794**Number:****Order** MC150T7.5/DE/830**Abbreviation:**

General 150W POWERBALL Double ended ceramic metal halide lamp, pulse
Description: start, high CRI, reduced color shift, R7S base, T7, enclosed fixture rated, universal operation, clear, 3000K.

Product Information

Abbrev. With Packaging Info.	MC150T75DE830 12/CS 1/SKU
ANSI Code	M 102/E:M 142/E:M 81E
Approx. Lumens (initial - horizontal)	14800
Approx. Lumens (mean - horizontal)	11840
Approx. Lumens (mean - horizontal) 2	11840
Arc Length (in)	0.36
Arc Length (mm)	9.2
Average Rated Life - Horizontal (hr)	15000
Average Rated Life - (hr)	15000
Avg Rated Life (hrs)	12000
Base	R7S RSC
Bulb	T7.5
Color Rendering Index (CRI)	91
Color Temperature/CCT (K)	3000
Diameter (in)	0.906
Diameter (mm)	23.00
Family Brand Name	POWERBALL® CERAMIC METALARC® TUBULAR DOUBLE-ENDED
Fixture Requirement	E
Hot Restrike Time (min)	2-15
Lamp Finish	Clear
Light Center Length - LCL (in)	2.6
Light Center Length - LCL (mm)	66
Maximum Base Temperature - Fahrenheit	536
Maximum Base Temperature - Celsius	280
Maximum Bulb Temperature - Fahrenheit	650
Maximum Bulb Temperature -	

Celsius	1202
Maximum Overall Length - MOL (in)	5.2
Maximum Overall Length - MOL (mm)	132
Nominal Voltage (V)	95.00
Nominal Wattage (W)	150.00
Operating Position	HORIZONTAL +/- 45 DEGREES
Warm-up Time (min)	2-4



Footnotes

- Consult your OSRAM SYLVANIA Lighting Representative for compatible electronic operating systems.
- Use with 4000V pulse rated sockets only.
- E = Lamps classified as E-type are to be used ONLY in suitably enclosed luminaries. See lamp warning.
- UV-Stop quartz
- Lamps may be operated on ANSI M142 or M81 Compliant ballasts.