

**Product** 64972**Number:****Order** MC70T6/DE/830**Abbreviation:**

General METALARC POWERBALL 70W ceramic metal halide double ended,
Description: clear, universal operation, RSC base, 3000K CCT, 88 CRI, pulse start, enclosed rated, 15,000 hour rated life

Product Information

Abbrev. With Packaging Info.	MC70T6DE830 12/CS 1/SKU
Approx. Lumens (initial - horizontal)	7000
Approx. Lumens (initial - vertical)	6600
Approx. Lumens (mean - horizontal)	5280
Approx. Lumens (mean - vertical)	5280
Arc Length (in)	0.29
Arc Length (mm)	7.4
Base	RX7S
Bulb	T19
Color Rendering Index (CRI)	88
Color Temperature/CCT (K)	3100
Diameter (in)	0.787
Diameter (mm)	20.00
Family Brand Name	POWERBALL® CERAMIC METALARC® TUBULAR SINGLE-ENDED
Fixture Requirement	E
Hot Restrike Time (min)	2-15
Light Center Length - LCL (in)	2
Light Center Length - LCL (mm)	52
Maximum Base Temperature - Fahrenheit	572
Maximum Bulb Temperature - Fahrenheit	842
Maximum Overall Length - MOL (in)	3.19
Maximum Overall Length - MOL (mm)	81
Nominal Voltage (V)	92.00
Nominal Wattage (W)	70.00
Operating Position	Universal
Warm-up Time (min)	2-4 min

**Footnotes**

- Consult your OSRAM SYLVANIA Lighting Representative for compatible electronic operating systems.
- Use with 4000V pulse rated sockets only.
- E = Lamps classified as E-type are to be used ONLY in suitably enclosed luminaries. See lamp warning.
- Lamp requires a nominal Open Circuit Voltage of 230V or higher. Without an ignitor in the circuit minimum OCV is 209Vrms.
- Lamps may be operated on ANSI M98 Compliant Ballast.
- UV-Stop quartz
- Lamps may be operated on ANSI M85 or M98 Compliant ballasts.
- Approved electronic ballast is required, view approved ballast list in Product documents, graphs and images.