





GE
Lighting

25218 - MVR175/PAR38/FL1

GE Multi-Vapor® Quartz Metal Halide PAR38



CAUTIONS & WARNINGS

R- WARNING: This lamp can cause serious skin burn and eye inflammation from shortwave ultraviolet radiation if outer envelope of the lamp is broken or punctured, and the arc tube continues to operate. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Certain types of lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available. Visit the FDA website for more information: <http://www.fda.gov/cdrh/radhealth/products/urburns.html>

Caution

- Lamp may shatter and cause injury if broken
 - Dispose of lamp in a closed container.
 - Do not use excessive force when installing lamp.
 - Do not use lamp if outer glass is scratched or broken.

Warning

- Unexpected lamp rupture may cause injury, fire, or property damage
 - Do not exceed rated voltage.
 - Do not turn on lamp until fully installed.
 - Do not use beyond rated life.
 - Do not use lamp if outer glass is scratched or broken.
 - Do not use where directly exposed to water or outdoors without an enclosed fixture.
 - If used on a dimming system, see instructions.
 - Operate lamp only in specified position.
 - Turn lamp off at least once for 15 minutes per week.
 - Use in enclosed fixture rated for this product.
 - Use only properly rated ballast.
- A damaged lamp emits UV radiation which may cause eye/skin injury
 - Turn power off if glass bulb is broken. Remove and dispose of lamp.
- Risk of Burn
 - Allow lamp to cool before handling.
 - Do not turn on lamp until fully installed.
- Risk of Electric Shock
 - Do not use where directly exposed to water or outdoors without an enclosed fixture.
 - Turn power off before inspection, installation or removal.
- Risk of Fire
 - Keep combustible materials away from lamp.
 - Use in fixture rated for this product.

GRAPHS & CHARTS

Graphs_Spectral Power Distribution

GENERAL CHARACTERISTICS

Lamp Type	High Intensity Discharge - Quartz Metal Halide
Bulb	PAR38
Base	Medium Screw (E26)
Bulb Finish	Clear
Rated Life (Vert)	7500.0 h
Rated Life (NOM)	7500.0 h
Bulb Material	Hard glass
Lamp Enclosure Type (LET)	Enclosed fixtures only
Mercury Content (NOM)	23.76 mg
Picograms of Mercury (NOM)	264.0 pg

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (Vert)	12000.0
Initial Lumens (NOM)	12000.0
Nominal Initial Lumens per Watt (NOM)	69.0
Beam Spread (NOM)	25.0 °
Center Beam Candlepower (CBCP) (NOM)	6500.0
Color Temperature (NOM)	3800.0 K
Color Rendering Index (CRI) (NOM)	65.0

ELECTRICAL CHARACTERISTICS

Wattage (NOM)	175.0
Burn Position	Universal burning position
Open Circuit Voltage (peak lead ballast) (MIN)	540.0 V
Open Circuit Voltage (RMS lag ballast) (MIN)	382.0 V
Warm Up Time to 90% (MIN)	2.0 min
Warm Up Time to 90% (MAX)	5.0 min
Hot Restart Time to 90% (NOM)	10.0 min

DIMENSIONS

Maximum Overall Length (MOL) (NOM)	5.620 in(142.7 mm)
Nominal Length (NOM)	5.620 in(142.7 mm)
Bulb Diameter (DIA) (NOM)	4.750 in(120.6 mm)

PRODUCT INFORMATION

Product Code	25218
Description	MVR175/PAR38/FL1
ANSI Code	M57
Standard Package	Case
Standard Package GTIN	10043168252185
Standard Package Quantity	6
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	6
UPC	043168252188

