



GE  
Lighting

## 14636 - 200PS30/CVG


GE covRguard® PS30 - Shatter-Resistant

• Coating is shatter and weather-resistant. Resists breakage from heat and thermal shock that can occur from water, sleet, snow, molten solder, and weld spatter. Rough service version available for extra tough conditions.

**This product is no longer manufactured.**

Photo  
Not Available

Photo  
Not Available



### CAUTIONS & WARNINGS

#### Warning

- Risk of Fire
  - Keep combustible materials away from lamp.

### NOTES

- Lamp base is a brass base (BB).
- Will operate in any burning position, but fixed-socket usage other than base up or continuous burning in any position in ambient temperatures above 150 degrees F (66 degrees C), may result in some loss of protective coating. Reflectors and accessories may raise bulb temperature and cause some loss of protective coating.

### GENERAL CHARACTERISTICS

Lamp Type	Incandescent - A-line
Bulb	PS30
Base	Medium Screw (E26)
Filament	C-9
Bulb Finish	Inside frost
Rated Life (NOM)	1000.0 h
Bulb Material	Soft glass
Base Material	Brass
Primary Application	Shatter-Resistant

### PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	3480.0
Nominal Initial Lumens per Watt (NOM)	17.4

### ELECTRICAL CHARACTERISTICS

Wattage (NOM)	200.0
Voltage (NOM)	120.0

### DIMENSIONS

Maximum Overall Length (MOL) (NOM)	8.060 in(204.7 mm)
Bulb Diameter (DIA) (NOM)	3.750 in(95.2 mm)
Light Center Length (LCL) (NOM)	6.000 in(152.4 mm)

### PRODUCT INFORMATION

Product Code	14636
Description	200PS30/CVG
Standard Package	Case
Standard Package GTIN	10043168146361
Standard Package Quantity	60
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	60
UPC	043168146364