

PAR30 LED with AirFlux Technology

13PAR30S/END/F36 3000 DIM SM 6/1

Philips PAR30 Dimmable LED Lamps with AirFlux Technology provide optimal thermal efficiency in a sleek, lightweight design.

Product data

• General Characteristics

Cap-Base

Bulb PAR30S [PAR30S mm]

Bulb Finish White Rated Avg. Life 45000 hr

(Hours)

Nominal Lifetime 45000 hr

hours

• Light Technical Characteristics

Color Code WH Color Designation White 36 D Beam Angle

36D [Medium beam] Beam Description 3000 K

Correlated Color Temperature

Approximate Lumens

750 Lm 1550 cd Approx. MBCP CRI 80 Luminous Efficacy 57.69 Lm/W

Lamp

Color Temp. (Kelvin) 3000 K [CCT 3000K]

Rated Luminous Flux 750 Lm LLMF - end nominal 70 %

lifetime

Colour consistency 6 steps Rated Beam Angle 36 D

• Electrical Characteristics

13 W Wattage Wattage Technical 13 W 120 V Voltage Line Frequency 60 Hz Power Factor 0.8 -150 mA Lamp Current mA

Dimmable Yes Wattage Equivalent Rated Wattage 60 W 13.0 W Starting Time 0.5 s Warm-up Time to instant full light

Yes

60% Light Outp

Suitable for accent

lighting

• Temperature Characteristics

71 C T-case maximum

• Environmental characteristics

Energy Efficiency Label (EEL)

• Measuring Conditions

50000X Switching cycle

Product Dimensions

Overall Length C 88.8 mm Overall Length C 3.50 (max) in [inch]

92 mm Diameter D

• Product Data

Product number 423475

13PAR30S/END/F36 3000 DIM SM Full product name

13PAR30S/END/F36 3000 DIM SM Short product name

6/1

Pieces per Sku 1






PAR30 LED with AirFlux Technology

eop_pck_cfg 6 Skus/Case 6

Bar code on pack 46677423476

Bar code on case 50046677423471 Logistics code(s) 929000228704 eop_net_weight_pp 0.310 kg

Dimensional drawing



13PAR30S/END/F36 3000 DIM SM 6/1

Product	C (Norm)	C1 (Max)	D (Norm)	D1 (Norm)
LED 13W 3000K 120V PAR30S 36D	88.8	3.50	92	3.62



E26



Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.