

DOWN LIGHTING SERIES

4 INCH 9W Ra80

Greenlux LED



DL4009DIM098027K
DL4009DIM098030K
DL4009DIM098050K



PRO

- ★ Low energy consumption
- ★ Efficient LED replacement for halogen bulbs
- ★ Improved color rendering
- ★ No UV radiation
- ★ Especially suitable for public areas like lobbies
- ★ Suitable for commercial and residential lighting



LM 79

LM 80

9W REPLACE



75W

Halogen

80% Energy Savings

\$330 Energy Saving Per Lamp*

750
LM
BRIGHTNESS

DIMMABLE

83
LPW
EFFICACY


5
YR
WARRANTY

80
CRI(Ra)

50,000
H



- ★ We use innovative, specially designed reflector and PC cover to optimize beam distribution.
- ★ This reflector and PC cover create soft, pleasant light, with low glare.
- ★ The reflector and PC cover design provides high luminescence with an even beam pattern.



- ★ Unique heat sink design.
- ★ Seamless aluminum and structure design to reduce the operating temperature of the LED chips.
- ★ Excellent heat sink guarantees a longer life.



10 Industrial Rd Richland, MO 65556

Toll Free: (800) 624-4568 Local: (573) 765-5219 Fax: (800) 747-0999

DOWN LIGHTING SERIES

4 INCH 9W Ra80

Greenlux LED

GENERAL LIGHTING





RECESSED LIGHTING



ACCENT LIGHTING



ILLUMINANCE



SPECIFICATION

Product Model	DL4009DIM098027K	DL4009DIM098030K	DL4009DIM098050K
Type	Down Light 4	Down Light 4	Down Light 4
SKU#	8000619	8000626	8000640
Base	E26/GU24	E26/GU24	E26/GU24
Power(W)	9W	9W	9W
Voltage-Frequency	120V 60Hz	120V 60Hz	120V 60Hz
Color Temperature	Soft White 2700K	Warm White 3000K	Daylight 5000K
Ra	>80	>80	>80
Typical Lumen(lm)	750lm	750lm	750lm
Efficacy	83	83	83
Beam Angle	100°	100°	100°
Dimmable	YES	YES	YES
Power Factor	>0.9	>0.9	>0.9
Life time	50000H	50000H	50000H
Replace	75W	75W	75W