




GE  
Lighting

## 20122 - 200PAR

GE PAR56 - Train; Very Narrow Spot; Locomotive

Photo  
Not Available



### CAUTIONS & WARNINGS

#### Warning

- Risk of Fire
  - Keep combustible materials away from lamp.
- Risk of Electric Shock
  - Turn power off before inspection, installation or removal.
- Unexpected lamp rupture may cause injury, fire, or property damage
  - Use in enclosed fixture rated for this product.
  - Avoid direct water/liquid contact.

### NOTES

- Burning position-horizontal.
- Lamp is made of heat resistant glass (HRG).

### GENERAL CHARACTERISTICS

Lamp Type	Sealed Beam - PAR
Bulb	PAR56
Base	Screw Terminals
Filament	CC-8
Rated Life (NOM)	350.0 h
Primary Application	Train;Very Narrow Spot;Locomotive

### PHOTOMETRIC CHARACTERISTICS

Beam Spread - Horizontal	9.0 - 10.0 °
Beam Spread - Vertical	9.0 - 10.0 °
Center Beam Candlepower (CBCP) (NOM)	230000.0

### ELECTRICAL CHARACTERISTICS

Wattage (NOM)	200.0
Voltage (NOM)	30.0

### DIMENSIONS

Maximum Overall Length (MOL) (NOM)	4.500 in(114.3 mm)
Bulb Diameter (DIA) (NOM)	7.000 in(177.8 mm)

### PRODUCT INFORMATION

Product Code	20122
Description	200PAR
Standard Package	Case
Standard Package GTIN	10043168201220
Standard Package Quantity	12
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard	12
Package	
UPC	043168201223