



# 16481 - 892 GE T3.25 (T3 1/4) - Automotive





### **CAUTIONS & WARNINGS**

### Caution

#### Risk of Burn

- Allow lamp/fixture to cool before handling.

#### Warning

- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
- Avoid direct water/liquid contact.
- Dispose of lamp in a closed container.
- Do not exceed rated voltage.
- Do not turn on lamp until fully installed.
- Do not use lamp if outer glass is scratched or broken.
- Keep children away.
- Use eye protection when handling lamp.
- Use in enclosed fixture rated for this product.
- Use protective screen when handling.

### **GENERAL CHARACTERISTICS**

Lamp Type Bulb Base Filament Rated Life (NOM) **Bulb Material** Atmosphere **Primary Application** 

Miniature - T & TL Shape T3.25 (T3 1/4) Axial Plastic (PG13) C-6 300.0 h Hard glass Gas-filled High Mount Stop;Back up

# **PHOTOMETRIC CHARACTERISTICS**

Initial Lumens (NOM) 352.0 Nominal Initial Lumens per Watt 22.0 (NOM) Mean Spherical Candlepower 28.0 (MSCP) (NOM)

## **ELECTRICAL CHARACTERISTICS** Wattage (NOM)

Wattage (NOM)	16.0
Voltage (NOM)	12.8

# DIMENSIONS

Maximum Overall Length 2.680 in(68.1 mm) (MOL) (NOM) Bulb Diameter (DIA) (NOM) 0.406 in(10.3 mm) Light Center Length (LCL) (NOM)

1.000 in(25.4 mm) 16/81

### **PRODUCT INFORMATION** Product Code

Product Code	16481
Description	892
ANSI Code	892
Standard Package	Case
Standard Package GTIN	00043168164818
Standard Package Quantity	10
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard	10
Package	
UPC	043168963589

Apr 14, 2014 5:00:58 PM For additional information, visit www.gelighting.com