




GE
Lighting

25150 - 9003NH/BP

GE NIGHTHAWK™ T4.75 (T4 3/4) - Automotive



CAUTIONS & WARNINGS

Warning

- Risk of Burn
 - Allow lamp/fixture to cool before handling.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
 - Dispose of lamp in a closed container.
 - Do not exceed rated voltage.
 - Do not touch glass with bare hands.
 - Do not turn on lamp until fully installed.
 - Do not use lamp if outer glass is scratched or broken.
 - Keep children away.
 - Use eye protection when handling lamp.
 - Use protective screen when handling.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
 - Avoid direct water/liquid contact.
 - Dispose of lamp in a closed container.
 - Do not exceed rated voltage.
 - Do not turn on lamp until fully installed.
 - Do not use lamp if outer glass is scratched or broken.
 - Keep children away.
 - Use eye protection when handling lamp.
 - Use in enclosed fixture rated for this product.
 - Use protective screen when handling.

GENERAL CHARACTERISTICS

Lamp Type	Miniature - T & TL Shape
Bulb	T4.75 (T4 3/4)
Base	P43T-38
Filament	C-8/C-8
Rated Life (NOM)	150.0/800.0 h
Atmosphere	Gas-filled
Primary Application	Headlamp-Low beam only; Fog/Driving; Headlamp-High/Low beam; Headlamp-High beam only

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	1736.0 /995.0
Nominal Initial Lumens per Watt (NOM)	25.91045 /16.58333
Mean Spherical Candlepower (MSCP) (NOM)	119.0 /72.0

ELECTRICAL CHARACTERISTICS

Wattage (NOM)	67.0
Voltage (NOM)	12.8

DIMENSIONS

Maximum Overall Length (MOL) (NOM)	3.620 in(91.9 mm)
Bulb Diameter (DIA) (NOM)	0.625 in(15.9 mm)
Light Center Length (LCL) (NOM)	1.120 in(28.4 mm)

PRODUCT INFORMATION

Product Code	25150
Description	9003NH/BP
ANSI Code	9003
Standard Package	Master
Standard Package GTIN	10043168251508
Standard Package Quantity	24
Sales Unit	Blister
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	24
UPC	043168251501