


### 43760 - 784

GE T2.25 (T2 1/4) - Low Voltage; Emergency Building; Emergency Building Light







#### **CAUTIONS & WARNINGS**

#### Caution

- Risk of Burn
- Allow lamp/fixture to cool before handling.

#### Warning

- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
- Avoid direct water/liquid contact.
- Dispose of lamp in a closed container.
- Do not exceed rated voltage.
- Do not turn on lamp until fully installed.
- Do not use lamp if outer glass is scratched or broken.
- Keep children away.
- Use eye protection when handling lamp.
- Use in enclosed fixture rated for this product.
- Use protective screen when handling.

## **GENERAL CHARACTERISTICS**

Lamp Type Miniature - T & TL Shape
Bulb T2.25 (T2 1/4)
Base 2-Pin (G4)
Filament C-6
Rated Life (NOM) 50.0 h
Bulb Material Hard glass

Primary Application Emergency Building;Low

Voltage

Gas-filled

#### PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM) 113.0 Nominal Initial Lumens per Watt 18.83333

(NOM)

Atmosphere

Mean Spherical Candlepower

(MSCP) (NOM)

9.0

### **ELECTRICAL CHARACTERISTICS**

Wattage (NOM) 6.0 Voltage (NOM) 6.0

### **DIMENSIONS**

Maximum Overall Length 1.000 in(25.4 mm)

(MOL) (NOM)

Bulb Diameter (DIA) (NOM) 0.281 in(7.1 mm) Light Center Length (LCL) 0.770 in(19.6 mm)

(NOM)

#### **PRODUCT INFORMATION**

Product Code 43760
Description 784
ANSI Code 784
Standard Package Case

Standard Package GTIN 20043168437602

Standard Package Quantity 10
Sales Unit Unit
No Of Items Per Sales Unit 1
No Of Items Per Standard 10

Package

UPC 043168437608

# NOTES

.028" metal pins spaced 44mm (.157") apart. GE's two-pin lamps might not be compatible with all G-4 sockets since many sockets do not provide clearance for the exhaust tip.