

89139 - 9003NHS/BP

GE NIGHTHAWK™ T4.75 (T4 3/4) - Automotive



CAUTIONS & WARNINGS

Warning

- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
 Avoid direct water/liquid contact.
- Dispose of lamp in a closed container.
- Do not exceed rated voltage.
- Do not turn on lamp until fully installed.
- Do not use lamp if outer glass is scratched or broken.
- Keep children away.
- Use eye protection when handling lamp.
- Use in enclosed fixture rated for this product.
- Use protective screen when handling.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
- Dispose of lamp in a closed container.
- Do not exceed rated voltage.
- Do not touch glass with bare hands.
- Do not turn on lamp until fully installed.
- Do not use lamp if outer glass is scratched or broken.
- Keep children away.
- Use eye protection when handling lamp.
- Use protective screen when handling.
- Risk of Burn
- Allow lamp/fixture to cool before handling.

GENERAL CHARACTERISTICS

Lamp Type Bulb Base Filament Rated Life (NOM) Atmosphere Primary Application Miniature - T & TL Shape T4.75 (T4 3/4) P43T-38 C-8/C-8 200.0/800.0 h Gas-filled Headlamp-Low beam only;Fog/Driving;Headlamp-High/Low beam;Headlamp-High beam only

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM) Nominal Initial Lumens per Watt (NOM) Mean Spherical Candlepower (MSCP) (NOM) Color Temperature (NOM)

119.0 /72.0

1736.0 /995.0

25.91045 /16.58333

3540.0 K

ELECTRICAL CHARACTERISTICS

Wattage (NOM) Voltage (NOM) 67.0 12.8

DIMENSIONS

Maximum Overall Length (MOL) (NOM) Bulb Diameter (DIA) (NOM) Light Center Length (LCL) (NOM) 3.620 in(91.9 mm) 0.625 in(15.9 mm) 1.120 in(28.4 mm)

PRODUCT INFORMATION

Product Code Description ANSI Code Standard Package Standard Package GTIN Standard Package Quantity Sales Unit No Of Items Per Sales Unit No Of Items Per Standard Package UPC

May 28, 2014 9:10:10 AM For additional information, visit www.gelighting.com