


# 10467 - 60PAR/HIR/FL40

#### GE HIR™ PAR38

- Up to 28% more efficient than standard halogen Up to 22% energy savings
- Up to 20% longer life -3000 hours

## a product of

# ecomagination-











## **CAUTIONS & WARNINGS**

#### Caution

- Lamp may shatter and cause injury if broken
- Do not use lamp if outer glass is scratched or broken.

## Warning

- Risk of Burn
- Allow lamp to cool before handling.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
- Do not use lamp if outer glass is scratched or broken.
- Risk of Fire
- Keep combustible materials away from lamp.
- Risk of Electric Shock
- Turn power off before inspection, installation or removal.

## **GENERAL CHARACTERISTICS**

Lamp Type Halogen - PAR

Bulb PAR38

Base Medium Skirt (E26/50x39)

Filament CC-8 Rated Life (NOM) 3000.0 h

Primary Application Indoor and outdoor

Floodlight

## PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM) 1050.0 Center Beam Candlepower 1700.0

(CBCP) (NOM)

Color Temperature (NOM) 2850.0 K Beam Spread (NOM) 40.0 ° Nominal Initial Lumens per Watt 17.5

(NOM)

## **ELECTRICAL CHARACTERISTICS**

Wattage (NOM) 60.0 Voltage (NOM) 120.0

## **DIMENSIONS**

Maximum Overall Length 5.313 in(135.0 mm)

(MOL) (NOM)

Bulb Diameter (DIA) (NOM) 4.750 in(120.6 mm)

#### PRODUCT INFORMATION

Product Code 10467

Description 60PAR/HIR/FL40

Standard Package Case

Standard Package GTIN 10043168104675

Standard Package Quantity

Sales Unit

No Of Items Per Sales Unit

No Of Items Per Standard

12

Package

UPC 043168104678