


17471 - 45PAR/H/FL25 6PK

GE energy-efficient halogen 45 watt PAR38 floodlight 1-pack

- GE energy-efficient halogen bulbs deliver crisp, white light. This unsurpassed light quality is ideal for adding depth, drama and interest to any outdoor space. These GE energy-efficient halogen floodlights use less energy than standard halogen bulbs, saving money on energy. GE energy-efficient halogen floodlights feature lenses designed to provide a precise beam pattern, dispensing broad beams of crisp, white light on your home's exterior and landscaping. Designed with a unique all-weather construction, they withstand harsh weather conditions better than regular bulbs. Use these bulbs in outdoor stake light and security fixtures and create a dramatic effect
- Designed with a unique all-weather construction, they withstand harsh weather conditions better than regular hulbs.
- Uses Halogen technology for a brighter, crisper light
- Lasts 25% longer than regular bulbs*
- GE's Floodlights cast a wider beam that adds drama to driveways and yards.
- Estimated yearly energy costs \$5.42 based on 3 hours per day \$0.11 per kWh
- · Lasts 2.3 years based on 3 hours per day usage
- PAR38 outdoor floodlight with medium base for use in security and wet rated fixtures

Energy Savings











CAUTIONS & WARNINGS

Caution

- Lamp may shatter and cause injury if broken
- Do not use lamp if outer glass is scratched or broken.

Warning

- Risk of Burn
- Allow lamp to cool before handling.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
- Do not use lamp if outer glass is scratched or broken.
- Risk of Fire
- Keep combustible materials away from lamp.
- Risk of Electric Shock
- Turn power off before inspection, installation or removal.

*20 month life based on rated life at 4 hours/day. Provides nearly the same light output (540 lumens vs. 600 lumens) as 50 watt, 2000 hr halogen bulb.

GENERAL CHARACTERISTICS

Lamp Type Halogen - PAR

Bulb PAR38

Base Medium Skirt (E26/50x39)
Filament CC-8

Rated Life (NOM) 2500.0 h

Primary Application Yard Stake;Indoor and outdoor Floodlight

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM) 540.0 Center Beam Candlepower 2000.0

(CBCP) (NOM)

 $\begin{array}{lll} \mbox{Color Temperature (NOM)} & 2750.0 \ \mbox{K} \\ \mbox{Beam Spread (NOM)} & 25.0 \ \mbox{°} \\ \mbox{Nominal Initial Lumens per Watt} & 12.0 \end{array}$

(NOM)

ELECTRICAL CHARACTERISTICS

Wattage (NOM) 45.0 Voltage (NOM) 120.0

DIMENSIONS

Maximum Overall Length 5.313 in(135.0 mm)

(MOL) (NOM)

Bulb Diameter (DIA) (NOM) 4.750 in(120.6 mm)

PRODUCT INFORMATION

Product Code 17471

Description 45PAR/H/FL25 6PK

Standard Package Case

Standard Package GTIN 00043168174718

Standard Package Quantity 6
Sales Unit Unit
No Of Items Per Sales Unit 1
No Of Items Per Standard 6

Package

UPC 043168970037