


# 18626 - 60PAR/HIR/FL30

## GE PAR38

- Up to 28% more efficient than standard halogen Up to 22% energy savings
- Up to 20% longer life -3000 hours


#### a product of

## ecomagination-





HALOGEN-IR



# CAUTIONS & WARNINGS

#### Caution

- Lamp may shatter and cause injury if broken
- Do not use lamp if outer glass is scratched or broken.

#### Warning

- Risk of Burn
- Allow lamp to cool before handling.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
  Do not use lamp if outer glass is scratched or broken.
- Risk of Fire
- Keep combustible materials away from lamp.
- Risk of Electric Shock
- Turn power off before inspection, installation or removal.

#### **GENERAL CHARACTERISTICS**

Lamp Type Bulb Base Filament Rated Life (NOM) Primary Application Halogen - PAR PAR38 Medium Skirt (E26/50x39) CC-8 3000.0 h Indoor and outdoor Floodlight

#### PHOTOMETRIC CHARACTERISTICS Initial Lumens (NOM) 1050.0

Initial Lumens (NOM) Center Beam Candlepower (CBCP) (NOM) Color Temperature (NOM) Beam Spread (NOM) Nominal Initial Lumens per Watt (NOM)

2850.0 K 30.0 ° 17.5

2800.0

#### **ELECTRICAL CHARACTERISTICS**

Wattage (NOM)	60.0
Voltage (NOM)	120.0

### DIMENSIONS

Maximum Overall Length (MOL) (NOM) Bulb Diameter (DIA) (NOM)

ength	5.313	in(135.0 mm)
) (NOM)	4.750	in(120.6 mm)

#### **PRODUCT INFORMATION**

Product Code Description Standard Package Standard Package GTIN Standard Package Quantity Sales Unit No Of Items Per Sales Unit No Of Items Per Standard Package UPC

043168900720