


20763 - 90PAR/FL25XL-OD

GE Floodlight PAR38

- Designed with a unique all-weather construction, they withstand harsh weather conditions better than regular bulbs.
- Uses Halogen technology for a brighter, crisper light
- Lasts 3 times longer than regular GE halogen bulbs*
- GE's Floodlights cast a wider beam that adds drama to driveways and yards.











CAUTIONS & WARNINGS

Caution

- Lamp may shatter and cause injury if broken
- Do not use lamp if outer glass is scratched or broken.

Warning

- Risk of Burn
- Allow lamp to cool before handling
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
- Do not use lamp if outer glass is scratched or broken.
- Risk of Fire
- Keep combustible materials away from lamp.
- Risk of Electric Shock
- Turn power off before inspection, installation or removal.
- *Guaranteed to last 4 years based on 4 hours use per day at 120V.

GENERAL CHARACTERISTICS

Lamp Type Halogen - PAR

Bulb PAR38

Base Medium Skirt (E26/50x39)

Filament CC-8 Rated Life (NOM) 6000.0 h

Primary Application Yard Stake;Indoor and outdoor Floodlight

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM) 1310.0 Center Beam Candlepower 4700.0

(CBCP) (NOM)

Color Temperature (NOM) 2800.0 K Beam Spread (NOM) 25.0 ° Nominal Initial Lumens per Watt 14.55556

(NOM)

ELECTRICAL CHARACTERISTICS

Wattage (NOM) 90.0 Voltage (NOM) 120.0

DIMENSIONS

Maximum Overall Length 5.310 in(134.9 mm)

(MOL) (NOM)

Bulb Diameter (DIA) (NOM) 4.750 in(120.6 mm)

PRODUCT INFORMATION

Product Code 20763

Description 90PAR/FL25XL-OD

Standard Package Case

Standard Package GTIN 10043168207635

Standard Package Quantity 6
Sales Unit Unit
No Of Items Per Sales Unit 1
No Of Items Per Standard 6

Package

UPC 043168207638