


# 40792 - 55PAR/HIR/FL40XL

### **GE HIR XL® PAR38**

- Up to 28% more efficient than standard halogen Up to 22% energy savings
- Up to 20% longer life -3000 hours

# a product of

# ecomagination-









# **CAUTIONS & WARNINGS**

#### Caution

- Lamp may shatter and cause injury if broken
- Do not use lamp if outer glass is scratched or broken.

# Warning

- Risk of Burn
- Allow lamp to cool before handling.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
- Do not use lamp if outer glass is scratched or broken.
- Risk of Fire
- Keep combustible materials away from lamp.
- Risk of Electric Shock
- Turn power off before inspection, installation or removal.

# **GENERAL CHARACTERISTICS**

Lamp Type Halogen - PAR

Bulb PAR38

Base Medium Skirt (E26/50x39)

Filament CC-8 Rated Life (NOM) 6000.0 h

Primary Application Indoor and outdoor

Floodlight

# PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM) 800.0 Center Beam Candlepower 2000.0

(CBCP) (NOM)

Color Temperature (NOM) 2680.0 K Beam Spread (NOM) 40.0 ° Nominal Initial Lumens per Watt 14.54545

(NOM)

# **ELECTRICAL CHARACTERISTICS**

Wattage (NOM) 55.0 Voltage (NOM) 120.0

# **DIMENSIONS**

Maximum Overall Length 5.313 in(135.0 mm)

(MOL) (NOM)

Bulb Diameter (DIA) (NOM) 4.750 in(120.6 mm)

#### PRODUCT INFORMATION

Product Code 40792

Description 55PAR/HIR/FL40XL

Standard Package Case

Standard Package GTIN 10043168407929

Standard Package Quantity 6
Sales Unit Unit
No Of Items Per Sales Unit 1
No Of Items Per Standard 6

Package

UPC 043168407922