

41545 - 45PAR30HIR/SP9XL

GE Compact HIR™ HIR XL® PAR30

- Up to 42% more efficient than standard halogen Up to 27% energy savings
- Up to 60% longer life -4000 hours

a product of ecomagination

Energy Savings

Photo Not Available Photo Not Available







CAUTIONS & WARNINGS

Caution

- Lamp may shatter and cause injury if broken
- Do not use lamp if outer glass is scratched or broken.

Warning

- Risk of Burn
- Allow lamp to cool before handling
- Risk of Fire
- Keep combustible materials away from lamp.
- Risk of Electric Shock
- Turn power off before inspection, installation or removal.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
- Do not use lamp if outer glass is scratched or broken.
- Do not use where directly exposed to water or outdoors without an enclosed fixture.

GENERAL CHARACTERISTICS

Lamp Type Halogen - PAR
Bulb PAR30
Base Medium NP
Filament CC-8
Rated Life (NOM) 6000.0 h
Primary Application Ceiling Fan

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM) 620.0 Center Beam Candlepower 9750.0

(CBCP) (NOM)

Color Temperature (NOM) 2680.0 K Beam Spread (NOM) 9.0 ° Nominal Initial Lumens per Watt 13.77778

(NOM)

ELECTRICAL CHARACTERISTICS

Wattage (NOM) 45.0 Voltage (NOM) 120.0

DIMENSIONS

Maximum Overall Length 3.620 in(91.9 mm)

(MOL) (NOM)

Bulb Diameter (DIA) (NOM) 3.750 in(95.2 mm)

PRODUCT INFORMATION

Product Code 41545

Description 45PAR30HIR/SP9XL

Standard Package Case

Standard Package GTIN 10043168415450

Standard Package Quantity
Sales Unit
No Of Items Per Sales Unit
No Of Items Per Standard

15

Package

UPC 043168415453