

46166 - 60PAR/HIR/S/FL30

GE Silv-IR PAR38

• Up to 42% more efficient than standard halogen Up to 27% energy savings

• Up to 60% longer life -4000 hours

a product of

ecomagination

Energy Savings

Photo Not Available

Photo Not Available



CAUTIONS & WARNINGS

Caution

- · Lamp may shatter and cause injury if broken
- Do not use lamp if outer glass is scratched or broken.

Warning

- Risk of Burn
- Allow lamp to cool before handling.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage - Do not use lamp if outer glass is scratched or broken.
- Risk of Fire
- Keep combustible materials away from lamp.
- Risk of Electric Shock

- Turn power off before inspection, installation or removal.

GENERAL CHARACTERISTICS

Lamp Type Bulb Base Filament Rated Life (NOM) **Primary Application** Halogen - PAR PAR38 Medium Skirt (E26/50x39) CC-8 4000.0 h Indoor and outdoor Floodlight

PHOTOMETRIC CHARACTERISTICS 1050.0

Initial Lumens (NOM) Center Beam Candlepower (CBCP) (NOM) Color Temperature (NOM) Beam Spread (NOM) Nominal Initial Lumens per Watt (NOM)

ELECTRICAL CHARACTERISTICS 60.0 120.0

Universal burning position

2800.0

30.0 °

17.5

2800.0 K

DIMENSIONS

Wattage (NOM)

Voltage (NOM)

Burn Position

Maximum Overall Length (MOL) (NOM) Bulb Diameter (DIA) (NOM)

5.313 in(135.0 mm)

4.750 in(120.6 mm)

PRODUCT INFORMATION

Product Code Description Standard Package Standard Package GTIN Standard Package Quantity Sales Unit No Of Items Per Sales Unit No Of Items Per Standard Package UPC

043168461665